

SMS Interface



Introduction

The SMS Interface allows the user to send SMS messages (wireless text messages) from a Q-WIN or Q-MASTER system to GSM mobile phones. The SMS Interface consists of a system interface and a GSM modem. The package includes all units and cables needed to send SMS messages. SIM card not included.

Features

- Send SMS messages to mobile phones.
- Integrated SIM card reader.
- Dual band EGSM900 and GSM1800.

With the SMS Interface you can:

- Send alarms by SMS to staff or management when waiting times or other pre-set values exceed the limits set in Q-WIN or Q-MASTER.
- Receive automatic notifications by SMS when a customer has arrived for his or her appointment.
- Send SMS messages to customers informing them of the number of customers waiting ahead of them in a queue.



SMS Interface

Article Number

10112047

Used with

Q-WIN version 55.01q or later
BP2882 version 82.01q or later

Technical Data

Dimensions, system interface	102 x 101 x 52mm
Weight, system interface	145g
Dimensions, TC35 terminal	65 x 74 x 33mm
Weight, TC35 terminal	130g
Input voltage	24V
Operating Temperature	10°C - 32°C
Storage Temperature	-10°C - 40°C
Operating Humidity	15 - 85 % Rel. humidity
Storage Humidity	10 - 90 % Rel. humidity



Q-MATIC SWEDEN AB

Neongatan 8, SE-431 53 Mölndal, Sweden
Phone +46 31 756 46 00
Fax +46 31 756 46 99
Info@q-matic.se
www.q-matic.com

