

Q-MATIC TP3150™



The Q-MATIC TP3150 is the server printer in a Q-MATIC Solo System. It contains a complete system server for a powerful Queue Management System. The only time you need a PC is when you make changes to printer settings or want to read system information.

The printer has a built-in web server. Use any web browser connected to the same network to read information or to change settings.

Features

- Complete system server, compatible with almost all Q-MATIC hardware units (displays, workstation terminals, card reader interface, radio interface, etc.).
- Ethernet connection.
- Web server.
- Thermal print head, no ink or toner.
- 1-5 ticket buttons.
- Supports all languages (fonts are downloaded to the printer).
- Tactile buttons.
- Five reports in PDF format.
- One management screen.
- Web-based workstation terminal.
- Easy to use ticket editor as a separate PC application.
- Can be modified to become a ticket printer for Q-WIN systems.

With the Q-MATIC TP3150™ you can

- Run a complete Queue Management System with displays, workstations, statistical reports, etc.

Q-MATIC TP3150™

Article number

10213051

Connection

TCP/IP, Q-MATIC 1745

Technical Specifications

Width	174 mm
Height	182 mm
Depth	300 mm
Weight	1.040 kg
Power Supply	External 24 V, 4 A
Minimum bandwidth	10 Mbit/s
Supported bandwidth	10/100 Mbit/s
Power Consumption, stand by	4 W
Power Consumption, printing	$W_{\max} = 104 \text{ W}$, $T_{\max} = 1 \text{ sec}$
Operating Temperature	10-40 °C
Storage Temperature	0-40 °C
Operating Humidity	15-75 % relative humidity
Storage Humidity	10-90 % relative humidity

Complies with the following standards:

CE

DS135.01A

